

We've got you covered!

Whether the job calls for a glamour clear, high speed production clear, or a V.O.C. compliant clear... look no further.

Transtar offers a full complement of Clearcoat products that will give you the great finish you've come to expect.



TRANSTAR[®]

AUTOBODY TECHNOLOGIES, INC.



2040 Heiserman Drive • Brighton, MI 48114
TEL: (800) 824-2843 • FAX: (800) 477-7923
email: info@tat-co.com
www.tat-co.com

Transtar Clearcoats offer reliability, versatility and consistent quality. Here are just a few of the salient features of the Transtar Clearcoat line:

- Compatible with most solvent and waterborne basecoats
- Can be used over single stage topcoats
- Compatible with both HVLP and conventional spray equipment
- Can be used in air dry or force dry situations
- Suitable for automobiles, trucks and equipment

2.1 Low V.O.C. Clearcoat

Finish-Tec® 6531 Clear is an acrylic urethane clearcoat with a sprayable V.O.C. of 2.1#/gal (using EPA Test Method 24) for spot, panel and overall refinishing. This product can be used with all solvent based and water based basecoats.

TECH DATA	% SOLIDS (RTU): 34% by weight
	V.O.C. Content: 2.1#/gal (252 g/l) Ready to Spray
	MIX RATIO: (4:1) 4 parts clearcoat to 1 part 6800 series activator



Kwik Finish 2.1 Clearcoat

Finish-Tec® Kwik Finish 2.1 Clearcoat is an acrylic urethane clearcoat with a sprayable V.O.C. of 2.1#/gal (using EPA Test Method 24) for spot, panel and overall refinishing. This product can be used with all solvent based and water based basecoats. Kwik Finish 2.1 Clearcoat can be buffed in 2 hours at 75°F (24°C).

TECH DATA	% SOLIDS (RTU): 34% by weight
	V.O.C. Content: 2.1#/gal (252 g/l) Ready to Spray
	MIX RATIO: (4:1) 4 parts clearcoat to 1 part 6800 series activator



Kwik Gloss Clearcoat

Finish-Tec® 4.2 Low V.O.C. Kwik Gloss Clearcoat is an acrylic urethane clearcoat with a sprayable V.O.C. of 4.2#/gal (using EPA Test Method 24) formulated for higher temperatures and bake booths. This product meets National Rule V.O.C. regulations of 5.0#/gal V.O.C. for basecoat/clearcoat characteristics and can be used with all solvent and water based basecoats. It is suitable for all automotive refinishing as well as trucks and equipment.

TECH DATA	% SOLIDS (RTU): 40% by weight
	V.O.C. CONTENT: 4.20#/gal (504 g/l) - Ready to Spray
	MIX RATIO: (4:1) 4 parts clearcoat to 1 part 6800 series activator

Hi-Gloss Clearcoat

Finish-Tec® Hi-Gloss Clearcoat is an acrylic urethane clearcoat formulated for higher temperatures and bake booths. Meets V.O.C. regulations of 5.0#/gal V.O.C. for multi-stage two part systems and can be used with all solvent and water based basecoats. Suitable for all automotive refinishing as well as trucks and equipment.

TECH DATA	% SOLIDS (RTU): 42% by weight
	VOC CONTENT: 4.20#/gal (504 g/l) - Ready to Spray
	MIX RATIO: (4:1) 4 parts clearcoat to 1 part 6800 series activator

MAX Clearcoat

Transtar's MAX Clearcoat is a super fast drying clearcoat that provides the additional features of low overspray and super high gloss. This unique product improves production by maximizing vehicle throughput. The fast flash feature provides the benefit of less dust and dirt getting trapped in the finish, which means less labor expended to buff or polish.

TECH DATA	% SOLIDS (RTU): 40% by weight
	V.O.C. CONTENT: 4.20#/gal (504g/l) Ready to Spray
	MIX RATIO: (4:1) 4 parts clearcoat to 1 part 6800 series activator

6800 Series Extra Solids Clearcoat Activators

Extra Solids Acrylic Urethane Clearcoat Activators are specifically designed for high productivity shops using Transtar Finish-Tec® Clearcoats. Activators are suitable for use in clearcoat applications over single stage topcoats and for base/clear applications (except lacquers).

TECH DATA	Lightning: For use under 70°F (21°C)
	Spot & Panel: 65 - 80°F (19 - 27°C)
	Overall: 75 - 90°F (24 - 32°C)
	Hi-Temp: For larger jobs in temperatures exceeding 75°F (24°C)

Euro Classic Clearcoat

Euro Classic Clearcoat is designed for applications requiring the ultimate finish appearance. This high solids clearcoat provides optimum flow and leveling, and imparts a glass-like finish. It has excellent flexibility and is resistant to stone chips and abrasions. Ideal for use over single stage or base/clear applications. May be used in air dry, downdraft, or force dry applications.

TECH DATA	% SOLIDS (RTU): 53% by weight
	V.O.C. CONTENT: 3.50#/gal (420g/l) Ready to Spray
	MIX RATIO: (2:1) 2 parts clearcoat to 1 part 7000 series activator

Euro Kwik Clearcoat

Euro Kwik Clearcoat is an acrylic urethane clearcoat designed for applications requiring the ultimate finish appearance. This product meets National Rule V.O.C. regulations of 5.0#/gal V.O.C. and Bay Area Rule 45 V.O.C. regulation of 4.5#/gal for Group 1 vehicles for basecoat/clearcoat systems and can be used with all solvent and waterborne basecoats. It is suitable for all automotive refinishing as well as trucks and equipment. Euro Kwik Clearcoat Urethane Clearcoat can be buffed in 2 hours at 75°F (24°C).

TECH DATA	% SOLIDS (RTU): 48% by weight
	V.O.C. CONTENT: 3.5#/gal (420 g/l) - Ready to Spray
	MIX RATIO: (2:1) 2 parts clearcoat to 1 part 7200 series activator

Euro Classic 2.1 Low V.O.C. Clearcoat

Finish-Tec® 7311 Euro Classic Clearcoat is designed for applications requiring the ultimate finish appearance. This high solids clearcoat provides optimum flow and leveling and imparts a glass-like finish. 7311 is an acrylic urethane clearcoat with a sprayable V.O.C. of 2.1#/gal (using EPA Test Method 24) for spot, panel and overall refinishing. This product can be used with all solvent based and water based basecoats.

TECH DATA	% SOLIDS (RTU): 41% by weight
	V.O.C. Content: 2.1#/gal (252 g/l) Ready to Spray
	MIX RATIO: (2:1) 2 parts clearcoat to 1 part 7300 series activator



Ordering Information:

6531	2.1 Low V.O.C. Clearcoat Gallon	2/case
6534	2.1 Low V.O.C. Clearcoat Quart	6/case
6571	Kwik Finish 2.1 Clearcoat Gallon	2/case
6574	Kwik Finish 2.1 Clearcoat Quart	6/case
6841	Kwik Gloss Clearcoat Gallon	2/case
6844	Kwik Gloss Clearcoat Quart	6/case
6854	Lightning Activator Quart	4/case
6861	Hi-Gloss Clearcoat Gallon	2/case
6874	Extra Solids Spot & Panel Activator Quart	4/case
6877	Extra Solids Spot & Panel Activator ½ Pint	12/case
6894	Extra Solids Overall Activator Quart	4/case
6894-HT	Extra Solids Overall Hi Temp Activator Quart	4/case
6897-HT	Extra Solids Overall Hi Temp Activator ½ Pint	12/case
7021	Euro Classic Clearcoat 5 Liter	2/case
7024	Euro Classic Clearcoat Quart	6/case
7086	Euro Classic Activator Fast 2.5 Liter	2/case
7088	Euro Classic Activator Fast Pint	12/case
7096	Euro Classic Activator Slow 2.5 Liter	2/case
7211	Euro Kwik Clearcoat 5 Liter	2/case
7214	Euro Kwik Clearcoat Quart	6/case
7226	Euro Kwik Activator Fast 2.5 Liter	2/case
7228	Euro Kwik Activator Fast Pint	12/case
7236	Euro Kwik Activator Slow 2.5 Liter	2/case
7311	Euro Classic 2.1 Low V.O.C. Clearcoat 5 Liter	2/case
7326	Euro Classic 2.1 Activator Fast 2.5 Liter	2/case
7336	Euro Classic 2.1 Activator Slow 2.5 Liter	2/case
7761-MTR	MAX Clearcoat Gallon	2/case
7764-MTR	MAX Clearcoat Quart	6/case

TRANSTAR®
AUTOBODY TECHNOLOGIES, INC.