

	Technology	Capacity (cfm FAD)	Max Pressure (psi)	Motor Size (HP)	Sound Level (dba)	Voltage/Phase	Operating Temp (°F)	Oil/Lubricant Carryover
Atlas Copco								
KT5, KT7.5, KT10	Piston	15-37	175	5-20	N/A	230v single-phase or 208-230-460 3-phase	N/A	N/A
	Rotary screw	10-170	175	3-50	61-72	230v single-phase or 208-230-460 3-phase	N/A	N/A
Champion								
R & PL Series	Reciprocating	5.3 to 102	250	1.5 to 30	N/A	115/208/230/1 208/230/460/575/3	100 max ambient temperature	< 2-3ppm
Curtis Toledo								
RS25	Rotary screw	108	150	25	70)	230/60	180	.3 ppm
Ingersoll Rand								
UP Series and R Series	Rotary screw	16-1650	65-200	5-300	65-71	230/1, 200/3, 230/3, 460/3, 575/3	35-104	0.01 mg/m3 (0.01 ppm)
Type 30 Series	Reciprocating	4.4-51.6	75-175	2-15	80-85	230/1, 200/3, 230/3, 460/3, 575/3	32-100	N/A
Kaeser								
SX 7.5 and SX 7.5 AirCenter	Rotary screw	28 at 125 psig	217	7.5	66	208-230,460/3ph	180-200	< 3ppm
SM 7.5 and SM 7.5 AirCenter	Rotary screw	32 at 125 psig	217	7.5	66	208-230,460/3ph	180-200	< 3ppm
SM 10 and SM 10 AirCenter	Rotary screw	42 at 125 psig	217	10	67	208-230,460/3ph	180-200	< 3ppm
SM 15 and SM 15 AirCenter	Rotary screw	53 at 125 psig	217	15	68	208-230,460/3ph	180-200	< 3ppm
SK 15 and SK 15 AirCenter	Rotary screw	71 at 125 psig	217	15	67	208-230,460/3ph	180-200	< 3ppm
SK 20 and SK 20 AirCenter	Rotary screw	88 at 125 psig	217	20	68	208-230,460/3ph	180-200	< 3ppm
AS 20 and AS 20 AirCenter	Rotary screw	92 at 125 psig	217	20	67	208-230,460/3ph	180-200	< 3ppm
AS 25 and AS 25 AirCenter	Rotary screw	111 at 125 psig	217	25	69	208-230,460/3ph	180-200	< 3ppm
AS 30 and AS 30 AirCenter	Rotary screw	124 at 125 psig	217	30	71	208-230,460/3ph	180-200	< 3ppm
Mattei								
AC 4	Vane	26	175	5	67	208-230-460-575/3, 230/1	170-200	1-3 ppm
AC 7	Vane	49	175	10	67	208-230-460-575/3	170-200	1-3 ppm
AC 11	Vane	74.5	175	15	67	208-230-460-575/3	170-200	1-3 ppm
AC 15	Vane	107	175	20	69	208-230-460-575/3	170-200	1-3 ppm
AC 18	Vane	130	175	25	69	208-230-460-575/3	170-200	1-3 ppm
AC 30	Vane	212	175	40	66	208-230-460-575/3	170-200	1-3 ppm
Quincy								
QT-54	Piston	15.2	175	5	74.1	230/1	104	< 5 PPM
QT-54	Piston	17.2	175	5	72.4	Tri-volt and 230/1	104	< 5 PPM
QT-7.5	Piston	22.6	175	7.5	75.7	Tri-volt and 230/1	104	< 5 PPM
QT-10	Piston	35	175	10	81.3	Tri-volt and 230/1	104	< 5 PPM
QT-15	Piston	51	175	15	80	Tri-volt	104	< 5 PPM
QT-30-20	Piston	75	175	20	84.6	Tri-volt	104	< 5 PPM
QT-30-25	Piston	92.4	175	25	84.6	Tri-volt	104	< 5 PPM
QT-30-30	Piston	105.9	175	30	84.6	Tri-volt	104	< 5 PPM
QGS5	Rotary screw	16.6	145	5	62	Tri-volt and 230/1	104	N/A
QGS7.5	Rotary screw	21.2	145	7.5	64	Tri-volt and 230/1	104	N/A
QGS10	Rotary screw	37	125	10	66	Tri-volt and 230/1	104	N/A
QGS15	Rotary screw	52	125	15	68	Tri-volt and 230/1	104	N/A
QGS20	Rotary screw	84	125	20	63	Tri-volt 3-phase	104	N/A
QGS25	Rotary screw	99	N/A	25	66	Tri-volt 3-phase	104	N/A
QGD20	Rotary screw	88	150	20	67	460/575	115	N/A
QGD258	Rotary screw	115	150	25	67	460/575	115	N/A
Sullivan Palatek								
M5	Rotary screw	15.5-22	175	5	70-75	200-230/1/60, 200-575/3/60	180	1 gallon
M7.5	Rotary screw	24-32	175	7.5	72-77	200-230/1/60, 200-575/3/60	180	1 gallon
M10	Rotary screw	32-38	175	10	75-78	200-575/3/60	180	1 gallon
15D	Rotary screw	54-55	150	15	72-78	200-575/3/60	180	3 gallon
25D4	Rotary screw	95	150	25	74-81	200-575/3/60	180	3 gallon
BendPak								
Tri-Max LS580V-501	Piston	22.8	175	5	75	208-230/1	33-104	< 3 ppm
Tri-Max LS580V-503	Piston	22.8	175	5	75	208-460/3	33-104	< 3 ppm
Tri-Max LS580V-601	Piston	22.8	175	5	75	208-230/1	33-104	< 3 ppm
Tri-Max LS580V-603	Piston	22.8	175	5	75	208-460/3	33-104	< 3 ppm
Tri-Max LS7580V-501	Piston	28.5	175	7.5	75	230/1	33-104	< 3 ppm
Tri-Max LS7580V-503	Piston	28.5	175	8	75	230-460/3	33-104	< 3 ppm
Tri-Max LS7580V-601	Piston	28.5	175	7.5	75	230/1	33-104	< 3 ppm
Tri-Max LS7580V-603	Piston	28.5	175	7.5	75	230-460/3	33-104	< 3 ppm
Hush Quiet LS15RS	Rotary screw	58	150	15	63	440/3	33-104	< 3 ppm